

Chapel Solar PV assessment

The page features three thick, lime green curved lines that form a partial circle around the central text. One line is at the top, one at the bottom, and one on the left side, all curving towards the center.

King's College


06.10.2022

MAX FORDHAM

Panel options

| Panel | Width (m) | Height (m) | Area (m ²) | Cell technology | Colour | Output (Wp) | Output density (Wp/m ²) |
|--------------------------------------|-----------|------------|------------------------|-----------------------------|------------------------|-------------|-------------------------------------|
| REC Alpha Pure 400 | 1.016 | 1.821 | 1.850136 | Heterojunction | black | 400 | 216 |
| REC Alpha Pure 410 | 1.016 | 1.821 | 1.850136 | Heterojunction | black | 410 | 222 |
| REC Alpha Pure-R 430 | 1.118 | 1.73 | 1.93414 | Heterojunction | black | 430 | 223 |
| REC Alpha 72 Series 450 | 1.026 | 2.063 | 2.116638 | Heterojunction | black with white frame | 450 | 213 |
| Polysolar - PS-CT - 10% transparency | 0.6 | 1.2 | 0.72 | Polyvinyl butyrate (PVB) | transparent | 72 | 100 |
| Polysolar - PS-CT - 50% transparency | 0.6 | 1.2 | 0.72 | Polyvinyl butyrate (PVB) | transparent | 40 | 56 |
| Bisol Spectrum - deep red | 1.05 | 1.77 | 1.8585 | 120 Half-Cut mono PERC c-Si | deep red | 320 | 172 |
| Kromatix - brass | 0.992 | 1.64 | 1.62688 | monocrystalline Si | brass | 255 | 157 |
| Kromatix - bronze | 0.992 | 1.64 | 1.62688 | monocrystalline Si | bronze | 255 | 157 |
| Colored Solar - Earth Brown | 0.99 | 1.652 | 1.63548 | Polycrystalline silicon | earth brown | 260 | 159 |
| Sunpower P3 COM - SPR P3 410 COM 15 | 0.998 | 2.066 | 2.061868 | Monocrystalline PERC | black | 410 | 199 |

- REC Alpha Pure 410
Selected on the basis of
 - High output density
 - Coordination with roof
 - All-black appearance
 - Commercial availability



PV shading and generation


| ☰ Shading by Field Segment | | | | | | | | | |
|--------------------------------|-------|---------|------------|------------------|-------------------------------|-----------------------|------------------|--------------|-----------------------|
| Description | Tilt | Azimuth | Modules | Nameplate | Shaded Irradiance | AC Energy | TOP ² | Solar Access | Avg TSRF ² |
| South Side Pitched Roof | 24.0° | 174.0° | 246 | 99.6 kWp | 913.5kWh/m ² | 74.3 MWh ¹ | 99.6% | 73.6% | 73.3% |
| North Side Pitched Roof | 24.0° | 354.0° | 246 | 99.6 kWp | 635.4kWh/m ² | 52.2 MWh ¹ | 60.0% | 84.9% | 51.0% |
| Totals, weighted by kWp | | | 492 | 199.3 kWp | 774.4kWh/m² | 126.4 MWh | 79.8% | 77.9% | 62.2% |

¹ approximate, varies based on inverter performance
² based on location Optimal POA irradiance of 1,245.5kWh/m² at 40.4° tilt and 182.6° azimuth

| ☰ Solar Access by Month | | | | | | | | | | | | |
|-------------------------------|---------|---------|---------|----------|----------|----------|----------|----------|----------|---------|---------|---------|
| Description | jan | feb | mar | apr | may | jun | jul | aug | sep | oct | nov | dec |
| South Side Pitched Roof | 62% | 69% | 68% | 72% | 80% | 82% | 81% | 77% | 67% | 66% | 63% | 62% |
| North Side Pitched Roof | 83% | 83% | 85% | 86% | 86% | 84% | 84% | 86% | 86% | 83% | 84% | 84% |
| Solar Access, weighted by kWp | 65.5% | 73.1% | 73.2% | 77.2% | 82.2% | 82.9% | 82.2% | 80.7% | 73.3% | 70.3% | 67.3% | 65.7% |
| AC Power (kWh) | 2,856.5 | 4,005.8 | 8,586.1 | 15,067.1 | 18,643.0 | 20,721.0 | 19,402.6 | 14,338.9 | 10,512.2 | 6,267.6 | 3,539.1 | 2,508.5 |

- Shading and output calculated for REC Alpha Pure 405 (available on HelioScope database), corrected for REC Alpha Pure 410

| Roof Slope | Rated panel output REC 405 | Annual output REC 405 | Rated panel output REC 410 | Annual output REC 410 |
|------------|----------------------------|-----------------------|----------------------------|-----------------------|
| | W | kWh/y | W | kWh/y |
| South | 405 | 74,300 | 410 | 75217.3 |
| North | 405 | 52,200 | 410 | 52844.4 |



Embodied carbon and carbon payback

- Embodied carbon of PV array (from [17094 \(willmottdixon.co.uk\)](http://willmottdixon.co.uk))
 - 710kg CO2/kWp
- Carbon payback periods
 - South slope – 4.5 years
 - North slope – 6.4 years




Figure 4 - Embodied carbon over 25 years
 Scenario 1: Project A, Flat roof, PV monocrystalline, Optimisers
 Scenario 2: Project B, Pitched roof, PV monocrystalline, Optimisers
 Scenario 3: Project B, Pitched roof, PV monocrystalline, No optimisers
 Scenario 4: Project B, Pitched roof, PV thin-film, No optimisers

| Roof Slope | Rated panel | Annual | Number of panels | Panel area | Array area | Array | | Embodied carbon | Embodied carbon | Carbon payback |
|------------|-------------|------------|------------------|------------|------------|--------|---------------|-----------------|-----------------|----------------|
| | output REC | output REC | | | | rated | Annual | | | |
| | 410 | 410 | | | | output | CO2 reduction | kg CO2/kWp | kg CO2 | y |
| | W | kWh/y | | m2 | m2 | kWp | kg CO2/y | | | |
| South | 410 | 75217.3 | 246 | 1.82 | 448 | 101 | 15969 | 710 | 71611 | 4.5 |
| North | 410 | 52844.4 | 246 | 1.82 | 448 | 101 | 11219 | 710 | 71611 | 6.4 |

Use of PV generated electricity

- Maximum peak output exceeds chapel demand
- Chapel demand is approximately 15% of main College demand
- The electrical supply to the chapel will be re-configured to ensure all generated energy is used within the main College site

